




Cube 2 Beryllium Chromium Zirconium Copper Sheet Alloy Strip

Our Product Introduction

Basic Information

- Place of Origin: china
- Brand Name: jinshunlai
- Certification: ISO, AISI, ASTM, GB, EN, DIN
- Model Number: 0.1nm-900nm
- Minimum Order Quantity: 1kg
- Price: Contact Us
- Packaging Details: Waterproof Paper, Steel Strip Packed and other Standard Export Seaworthy Package, or customized package
- Delivery Time: 5day
- Payment Terms: L/C, T/T , Western Union
- Supply Ability: 90000ton



Product Specification

- Coefficient Of Thermal Expansion: 17.2 $\mu\text{m}/\text{m}^\circ\text{C}$
- Density: 8.9g/cm³
- Electrical Resistivity: 0.15 $\mu\Omega\text{m}$
- Elongation: $\geq 20\%$
- Fatigue Strength: 150 MPa
- Hardness: HV ≤ 200
- Material: Chromium Zirconium Copper
- Melting Point: 1000
- Modulus Of Elasticity: 120 GPa
- Poisson's Ratio: 0.35
- Shear Modulus: 45 GPa
- Tensile Strength: $\geq 350\text{Mpa}$
- Thermal Conductivity: 170 W/mK
- Thickness: 0.5mm-3.0mm



More Images



for more products please visit us on copper-solid.com

Product Description

Typical Physical Properties of BrBNT1.9 (Qbe1.9) Copper Beryllium Alloy:

Density (g/cm³): 8.25

Elastic Modulus(Gpa): 130

Electrical Conductivity: 22-28% IACS

Thermal Expansion Coefficient(m/m): 17.5x10⁻⁶

Thermal Conductivity(25): 105W/m

Melting Point (°C): 870

mechanical And Electrical Properties of BrBNT1.9 (Qbe1.9) Copper Beryllium Strip:

Name	Temper	Thickness (mm)	Tensile Strength	Hardness	Elongation (min)
			MPa	HV	Percent
Qbe1.9	Soft	<0.15	>390	<120	>30%
		0.15~0.25	390~590		
		>0.25	390~590		
	Hard	<0.15	>590	>160	>3%
		0.15~0.25	590~880		
		>0.25	640~930		
	After Ageing (Soft)	<0.15	>1080	>330	>2%
		0.15~0.25	1080~1470		
		>0.25	1130~1470		
	After Ageing (Hard)	<0.15	>1080	>360	>1.5%
		0.15~0.25	1130~1570		
		>0.25	1170~1570		



copper
jin shun tai

Wuxi Jinnuo copper Co.,Ltd



+86-17763564398



sales01@shuangheyisteel.com



copper-solid.com

32 Chengnan Road, New District, Wuxi City, Jiangsu Province, China

