



Coiled Beryllium Copper Wire For Electricity Alloy 25 UNS C17200

Our Product Introduction

for more products please visit us on copper-solid.com

Basic Information

- Place of Origin: china
- Brand Name: jinshunlai
- Certification: IOS
- Model Number: 0.1mm-900mm
- Minimum Order Quantity: 1kg
- Price: contact us
- Delivery Time: 5day
- Payment Terms: L/C, T/T , Western Union,D/P
- Supply Ability: 90000ton



Product Specification

- Application: Electrical
- Color: Red
- Conductor Material: Copper
- Stranding: Solid
- Temperature Rating: 90°C
- Voltage Rating: 600V
- Wire Gauge: 14 AWG
- Color: Red Yellow
- Highlight: C17200 beryllium copper wire,
Coiled beryllium copper wire,
C17200 copper wire for electricity



More Images



Product Description

Alloy 25(UNS.C17200) Copper Beryllium Round Wires On Spools And In Coils

Product Specification:

UNS/CDA: C17200/ 172

DIN/EN: DIN2.1247 /CW101C

Others international specification: Alloy 25, JIS C1720, CuBe2, BeCu, BrB2

Chemical composition:

Be: 1.80-2.00%

Co +Ni: 0.20% Min

Co+Ni+Fe: 0.60% Ma

Cu: Balance

Cu+Be+Co+Ni+Fe: 99.5% Min

Typical Physical Properties of Alloy 25(UNS.C17200) Copper Beryllium Alloy:

Density (g/cm3):	8.36
Density before age hardening (g/cm3):	8.25
Elastic Modulus (kg/mm2 (103)):	13.4
Thermal Expansion Coefficient (20 °C to 200 °C m/m/°C):	17 x 10-6
Thermal Conductivity (cal/(cm-s-°C)):	0.25
Melting Range (°C):	870-980

International Specification of Alloy 25(UNS.C17200) Copper Beryllium Alloy:

Product Type	Temper Type
Bar	ASTM B196
	Military Mil-C-21657
Rod	ASTM B196
	Military Mil-C-21657
Wire	ASTM B197, AMS4725, SAE J461,463, RWMA Class 4
European Standards	CuBe2, Alloy 25, BrB2, DIN.2.1247, CW101C to EN

Note:

ASTM: American Society for Testing and Materials

SAE: Society of Automotive Engineers

AMS: Aerospace Materials Specification(Published by SEA)

RWMA: Resistance Welder Manufacturers' Association

Note: Unless otherwise specified, material will be produced by ASTM.

Key Technology of Beryllium Copper(Heat treatment)

Heat treatment is the most important process for this alloy system. While all copper alloys are hardenable by cold working, beryllium copper is unique in being hardenable by a simple low temperature thermal treatment. It involves two basic steps. The first is called solution annealing and the second, precipitation or age hardening.

Solution Annealing

For the typical alloy CuBe2Pb the alloy is heated between 720°C and 860°C. At this point the contained beryllium is essentially "dissolved" in the copper matrix (alpha phase). By rapidly quenching to room temperature this solid solution structure is retained. The material at this stage is very soft and ductile and can be readily cold worked by drawing, forming rolling, or cold heading. The solution annealing operation is part of the process at the mill and is not typically used by the customer. Temperature, time at temperature, quench rate, grain size, and hardness are all very critical parameters and are tightly controlled by ohmalloy.

Age Hardening

Age hardening significantly enhances the material's strength. This reaction is generally carried out at temperatures between 260°C and 540°C depending on alloy and desired characteristics. This cycle causes the dissolved beryllium to precipitate as a beryllium rich (gamma) phase in the matrix and at the grain boundaries. It is the formation of this precipitate which causes the large increase in material strength. The level of mechanical properties attained is determined by the temperature and time at temperature. It should be recognized that beryllium copper has no room temperature aging characteristics.

Fabrication

JOINING TECHNIQUE	SUITABILITY
Brazing	Good
Butt Weld	Fair
Capacity for Being Cold Worked	Excellent
Capacity for Being Hot Formed	Good
Coated Metal Arc Welding	Good
Gas Sheilded Arc Welding	Good
Machinability rating	50
Oxyacetylene Welding	Not Recommended
Seam Weld	Fair
Soldering	Good



Wuxi Jinnuo copper Co.,Ltd



+86-17763564398



sales01@shuangheyisteel.com



copper-solid.com

32 Chengnan Road, New District, Wuxi City, Jiangsu Province, China