china

IOS

jinshunlai

Hot Sale Copper Brass Foil Tape C26800 Brass Coil Strip 0.2mm 0.3mm 0.5mm Thickness Factory Direct

Basic Information


- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Delivery Time:
- Payment Terms:
- Supply Ability:
- 0.1mm-900mm 1kg contact us 5day L/C, T/T , Western Union,D/P 90000ton



Product Specification

- Width:
- Application:
- Processing Service:
- Surface:
- Thick:
- PAYMENT TERM:
- Material:
- Package:

50mm
Industrial, Electrical, Construction
Bending, Welding, Decoiling, Cutting, Punching
Bright
0.1-8mm
TT,LC
Copper, Brass
Wooden Box



More Images



Hot Sale Copper Brass Foil Tape C26800 Brass Coil Strip 0.2mm 0.3mm 0.5mm Thickness Factory Direct

Key attributes

Industry-specific attributes

Material	Brass strip
Cu (Min)	99.90%
Alloy Or Not	Non-Alloy


Lead Time

Quantity (kilograms)	1 - 5000	5001 - 10000	> 10000
Lead time (days)	5	10	To be negotiated

Other attributes

Place of Origin	Shandong, China
Application	electrical, industry, etc.
Width	as required.
Grade	C11000,C26800,etc
Brand Name	Jin Shunlai
Processing Service	Bending, Welding, Decoiling, Cutting, Punching
Product Name	99.9% Pure copper tape / strip / foil
Color	Copper-clored
Shape	pancake coil
Package	Sea Worthy Package
Delivery Time	within one week
Standard	ASTM GB JIS

Related products	copper foil copper tape copper coil
Keyword	99.9% Pure copper tape / strip / fol
Packaging & delivery	
Package Type:	Export standard packing or according to customers's requirement
Supply Ability	
Supply Ability	1000 Ton/Tons per Week
Product Description	



Туре	Brass coil,brass strip
Standard	EN13599
Material	Cu-ETPb Cu-FRHC° Cu-OF CuAg0,105 CuAg0,10P CuAg0,10(OF) Cu-PHC Cu-HCP
shape	disc
specification	thickness:0.1-8mm breadth: ≤1250mm
Surface treatment	mill,polished,bright,or as required.
package	Wooden box
Transit time	About 30 days
Payment method	TT, LC
Application	Electrical, industrial, construction, CARS

copper foil:

It has a strong wear resistance. It has high strength, strong hardness and chemical resistance. It also has prominent machining

mechanical performance.

It can be made for a variety of deepdrawn and bending force components, such as pins, rivets, washers, nuts, ducts, barometers,

screens, radiator parts.

It has good mechanical properties, good plasticity in hot state, the cold plastic is acceptable, good machinability, easy welding

and welding, corrosion, is a widely used material.



32 Chengnan Road, New District, Wuxi City, Jiangsu Province, China